

S5-GC(25-50)K-AU

Solis Three Phase Grid-Tied Inverters

Efficient

- Max. efficiency 98.8%
- String current up to 16A
- 4 MPPT design, supports multiple orientation system design
- Night time PID recovery function, increases overall system yield (optional)
- Wide voltage range and low startup voltage

Smart

- Support export power control
- Intelligent string monitoring, smart I-V curve scan
- Support RS485, WiFi, GPRS
- Scan to register on SolisCloud, support remote upgrade and control

Safe

- IP66
- AFCI protection, proactively reduces fire risk
- Globally recognised branded componentry for longer life
- Intelligent redundant fan-cooling

Economic

- Supports GPRS/WiFi communication with less wiring and reduced installation costs
- > 130% DC/AC ratio
- Supports high power modules for lower installation costs

Models:

S5-GC25K-AU / S5-GC30K-AU

S5-GC33K-AU / S5-GC36K-AU

S5-GC40K-AU / S5-GC40K-HV-AU

S5-GC50K-HV-AU



360° View



• Wi-Fi communication dongle included

DATASHEET

S5-GC(25-50)K-AU

Models	25K	30K	33K	36K	40K	40K-HV	50K-HV
Input DC							
Recommended max. PV power	33.3 kW	39.9 kW	43.9 kW	47.9 kW	53.2 kW	53.2 kW	66.5 kW
Max. input voltage				1100 V			
Rated voltage				600 V			
Start-up voltage				180 V			
MPPT voltage range				200-1000 V			
Max. input current				4*32 A			
Max. short circuit current				4*40 A			
MPPT number/Max. input strings number				4/8			
Output AC							
Rated output power	25 kW	30 kW	33 kW	36 kW	40 kW	40 kW	50 kW
Rated apparent output power	25 kVA	30 kVA	33 kVA	36 kVA	40 kVA	40 kVA	50 kVA
Max. apparent output power	25 kVA	30 kVA	33 kVA	36 kVA	40 kVA	40 kVA	50 kVA
Max. output power	25 kW	30 kW	33 kW	36 kW	40 kW	40 kW	50 kW
Rated grid voltage				3/N/PE, 230 V / 400 V			3/PE, 480 V
Rated grid frequency					50 Hz		
Rated grid current	41.8 A	50.2 A	55.1 A	60.2 A	66.9 A	53.0 A	66.2 A
Max. output current	41.8 A	50.2 A	55.1 A	60.2 A	66.9 A	53.0 A	66.2 A
Power factor				>0.99 (0.8 leading - 0.8 lagging)			
THDi					<3%		
Efficiency							
Max. efficiency		98.5%		98.6%		98.7%	98.8%
EU efficiency		98.1%		98.2%		98.3%	98.4%
Protection							
DC reverse-polarity protection					Yes		
Short circuit protection					Yes		
Output over current protection					Yes		
Surge protection					DC Type II / AC Type II		
Grid monitoring					Yes		
Anti-islanding protection					Yes		
Temperature protection					Yes		
Strings monitoring					Yes		
I/V Curve scanning					Yes		
Integrated AFCI 2.0					Optional		
Integrated PID recovery					Optional		
Integrated DC switch					Yes (PV2 Switch)		
General Data							
Dimensions (W*H*D)				647*629*252 mm			
Weight		38.2 kg				42.1 kg	
Topology				Transformerless			
Self-consumption (night)				<1 W			
Operating ambient temperature range				-25 ~ +60°C			
Relative humidity				0-100%			
Ingress protection				IP65			
Noise emission (typical)				≤60 dB (A)			
Cooling concept				Intelligent redundant fan-cooling			
Max. operation altitude				4000 m			
Grid connection standard				AS/NZS 4777.2:2020, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530			
Safety/EMC standard				IEC 62109-1/-2, IEC 61000-6-1/-2/-3/-4			
Features							
DC connection				MC4 connector			
AC connection				OT terminal			
Display				LCD			
Communication				RS485, Optional: Wi-Fi, GPRS			
Country of manufacture				China			